

## Winding machine VEN-L



## Ven-L suitable for winding several cables, tubes, flexible pipes and steelwire . Carrying capacity 200 kg. Equipped with:

- -Adjustable ring drum:
- outside diameter 950mm, core diameter adjustable 250mm 450mm, core width 0-300mm
- -Electrical drive 230 Volt
- -Step less speed control van 0 90 o.p.m. -Entry roller set for guiding the cable from the storage drum.
- -Length measuring meter type VEN-T cable passage 65mm with analogue counter manually movable for cable positioning. Hold to run button installed in the handle.
- -Machine mobile on 4 braked castor wheels (ø 125mm)
- -Length 2.100mm width 900mm height 1800mm
- -CE-marking

## **Options:**

- -Auxiliary parts for winding cable to small drums Max diameter 900 mm / max. Width 450mm (shaft hole 80 mm)
- -Bigger castor wheels
- -Auxiliary part for de-mounting the ringdrum as soon as it needs to wind on drums
- -Several other ring drums easily to connect to the drive
- -Mounted cable cutter for cutting the cable after winding
- -Several other lengtmeasuring meters

Venrooy Cable Equipment De Hork 35 5431 NS Cuijk

T 0485 33 60 33

E info@venrooy.nl

W www.venrooy.nl